

This listing of claims replaces all prior versions, and listings of claims in the instant application:

Listing of Claims:

1. (Currently amended) A method comprising:
adding direction to interference edges of a register interference graph, wherein each interference edge extends between two nodes of said register interference graph, said adding direction comprising:
for each node of each interference edge, determining whether a variable associated with said node was live when an other variable associated with the other node of said two nodes was defined or used;
wherein upon a determination that said variable associated with said node was live when said other variable associated with said other node was defined or used, said first node is a primary node; and
defining an interference edge adjacent a primary node as a pass edge;
defining a pass degree of each node as the number of pass edges of said node; and
choosing a node of said register interference graph to spill based upon [[a]] said pass degree of said node.
2. (Original) The method of Claim 1 further comprising building said register interference graph.
3. (Original) The method of Claim 1 wherein said register interference graph comprises:
a first node;
a second node; and
an interference edge between said first node and said second node, said first node being a primary node.

4. (Original) The method of Claim 3 wherein said second node is a secondary node.

5. (Original) The method of Claim 4 wherein said interference edge consists of a uni-directional interference edge.

6. (Original) The method of Claim 4 wherein an end of said interference edge adjacent said first node comprises a pass edge and wherein an end of said interference edge adjacent said second node comprises a non-pass edge.

7. (Original) The method of Claim 3 wherein said second node is a primary node.

8. (Original) The method of Claim 7 wherein said interference edge consists of a bi-directional interference edge.

9. (Original) The method of Claim 7 wherein an end of said interference edge adjacent said first node comprises a pass edge and wherein an end of said interference edge adjacent said second node comprises a pass edge.

10. (Original) The method of Claim 3 wherein a first variable associated with said first node is live when a second variable associated with said second node is defined or used.

11. (Currently amended) A method comprising:
building a register interference graph comprising defining an interference edge between a first node and a second node;
wherein upon a determination ~~determining~~ that a first variable associated with said first node is live when a second

variable associate with said second node is defined or used,
said first node is a primary node; and
defining an end of said interference edge adjacent said
first node as a pass edge;
defining a pass degree of said first node as a number of
pass edges of said first node; and
using said pass degree when choosing to spill a node from
said register interference graph.

12-13. (Canceled)

14. (Currently amended) A system comprising:
a processor; and
a memory having a method of allocating a set of variables
to a set of physical registers using selective spilling stored
therein, wherein upon execution of said method, said method
comprises:
building a register interference graph comprising defining
an interference edge between a first node and a second node;
wherein upon a determination ~~determining~~ that a first
variable associated with said first node is live when a second
variable associate with said second node is defined or used,
said first node is a primary node; and
defining an end of said interference edge adjacent said
first node as a pass edge;
defining a pass degree of said first node as a number of
pass edges of said first node; and
using said pass degree when choosing to spill a node from
said register interference graph.

15-16. (Canceled)

17. (Currently amended) A computer program product
having a method of allocating a set of variables to a set of

physical registers using selective spilling stored therein,
wherein upon execution of said method, said method comprises:

adding direction to interference edges of a register
interference graph, wherein each interference edge extends
between two nodes of said register interference graph, said
adding direction comprising:

for each node of each interference edge, determining
whether a variable associated with said node was live when
an other variable associated with the other node of said
two nodes was defined or used;

wherein upon a determination that said variable
associated with said node was live when said other
variable associated with said other node was defined or
used, said first node is a primary node; and

defining an interference edge adjacent a primary node
as a pass edge;

defining a pass degree of each node as the number of pass
edges of said node; and

choosing a node of said register interference graph to
spill based upon [[a]] said pass degree of said node.

18. (Original) The computer program product of Claim 17
wherein said method further comprises building said register
interference graph.

19. (Original) The computer program product of Claim 17
wherein said register interference graph comprises:

a first node;

a second node; and

an interference edge between said first node and said
second node, said first node being a primary node.

20. (Original) The computer program product of Claim 19
wherein said second node is a secondary node.

21. (Original) The computer program product of Claim 20 wherein said interference edge consists of a uni-directional interference edge.

22. (Original) The computer program product of Claim 20 wherein an end of said interference edge adjacent said first node comprises a pass edge and wherein an end of said interference edge adjacent said second node comprises a non-pass edge.

23. (Original) The computer program product of Claim 19 wherein said second node is a primary node.

24. (Original) The computer program product of Claim 23 wherein said interference edge consists of a bi-directional interference edge.

25. (Previously presented) The computer program product of Claim 23 wherein an end of said interference edge adjacent said first node comprises a pass edge and wherein an end of said interference edge adjacent said second node comprises a pass edge.

26. (Previously presented) The computer program product of Claim 19 wherein a first variable associated with said first node is live when a second variable associated with said second node is defined or used.

27. (Currently amended) A computer system comprising:
means for adding direction to interference edges of a register interference graph, wherein each interference edge extends between two nodes of said register interference graph,
said means for adding direction comprising:

for each node of each interference edge, a means for determining whether a variable associated with said node was live when an other variable associated with the other node of said two nodes was defined or used;

wherein upon a determination that said variable associated with said node was live when said other variable associated with said other node was defined or used, said first node is a primary node; and

a means for defining an interference edge adjacent a primary node as a pass edge;

a means for defining a pass degree of each node as the number of pass edges of said node; and

means for choosing a node of said register interference graph to spill based upon [[a]] said pass degree of said node.

28. (Original) The computer system of Claim 27 further comprising means for building said register interference graph.

29. (Original) The computer system of Claim 27 further comprising means for spilling said node.

30. (Canceled)